

is repaired. S	end copy to Depart	ment of Health; reta	ne regular monthly pre iin original in departme	iventive mainte nt file.	nance che	ck, and whenever instrum
20	1190				D	ATE OF INSPECTION
LOCATION OF INS	RUMENT (STREET AND CIT	(Y)				1-24-13
CHECKLIST:	Place a check (V)	LINDBERGH S	SUNSET HILLS MC	63127	''	ME OF INSPECTION 0809 IHRS
in observed va	lues where determi	ned.) Unchecked its	tem if found to be satis ems must be corrected	factory or if op	erating wi	0809 IHS. thin established limits. (W
	STIC CHECK (PRIN			belore dailig in	strument.	
□ сом						
			☑ DETEC	TOR		
☐ PROG			🗹 FILTER	s		,
HEAT	ERS SAMPLE CHAI	MBER <u>48</u> °C	QUART	Z STANDARD		
☐ FLOW	DETECTOR		☑ CALIBE			
/	HIGH SPEED				•	
_			PRINTE	R		
TIME AND	DATE 08	815 Itas.	1-26-13			
SIMULATO	R TEMPERATURE	(34 °C + 0.2°C)	24186			
V 044 100 4 74		(01 0 ± 0.2 0)				
TO CALIBHA [ON CHECK -					
Run three t	ON CHECK -	ard polition. All H				
Run three t	ests using a stand	ard solution. All the	oree tests must be wit	hin ± 5% of th	e standare	d value and must have a
Run three (spread of .0 RECIRCULA	ests using a stand 05 or less. Check t ATION PUMP)	·	o - mo otandaja 30	inguit pellig da	ed. (PRIN	d value and must have a
Run three to spread of .0 RECIRCULA 1 0.100% S	ests using a stand 05 or less. Check t ATION PUMP) TANDARD - MUST	READ RETWEEN	0050	iditori being us	e standarded. (PRIN	d value and must have a
Run three to spread of .0 RECIRCULA 1 0.100% S 1 0.040% S	ests using a stand 05 or less. Check t ATION PUMP) TANDARD - MUST TANDARD - MUST	READ BETWEEN O	0.095% and 0.105% INC	LUSIVE	e standarded ed. (PRIN	d value and must have a
Run three is spread of .0 RECIRCULA 0.100% S D 0.040% S (ONLY ONE	ests using a stand 05 or less. Check to ATION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO	READ BETWEEN O READ BETWEEN O BE USED PER MAI	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT)	LUSIVE	ea. (PRIN	d value and must have a TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S QUAO% S	ests using a stand 05 or less. Check to ATION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO	READ BETWEEN OF READ BETWEEN OF BE USED PER MAI	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT)	LUSIVE	e standarded. (PRIN	d value and must have a TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S ONLY ONE	ests using a stand 05 or less. Check to ATION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTEST 2	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT)	LUSIVE TES	ed. (PRIN	TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S ONLY ONE	ests using a stand 05 or less. Check to ATION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTEST 2	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT)	LUSIVE TES	ed. (PRIN	TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S (ONLY ONE ST 1 PERFORM R NUMBER OF FOLLOWS:	ests using a stand 05 or less. Check to ATION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO ### PARTICIPATION OF THE PRINTO REFUSALS, SINCE (DO NOT INCLUD	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTEST 2	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT)	LUSIVE TES	ed. (PRIN	TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S O.40% S ONLY ONE ST 1 PERFORM R NUMBER OF FOLLOWS:	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTENAN LAST MAINTENAN E SIMULATOR TEST	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT) 099 ICE REPORT, AND NU TS)	LUSIVE TES	T3 PT	OUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S ONLY ONE EST 1 PERFORM R NUMBER OF FOLLOWS:	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO ### PARTICIPATION OF THE PROPERTY OF THE PROP	READ BETWEEN OF READ BETWEEN O	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT) 099 ICE REPORT, AND NU TS)	LUSIVE TES	T3 PT	OUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S O.40% S O	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO ### ### ### ### ### ### ### ### ### #	READ BETWEEN OF READ BETWEEN O	0.095% and 0.105% INC 0.038% and 0.042% INC INTENANCE REPORT) 1099 INCE REPORT, AND NU TS) (.1014) 2 Idication that was made	LUSIVE TES MBER OF BREA (.1519)	T3 F	Over .19)
Run three is spread of .0 RECIRCULA 0.100% S O.40% S ONLY ONE EST 1 PERFORM R NUMBER OF FOLLOWS: FUSALS Of any new parts within establis	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO JOGS F.I. TEST (PRINTO REFUSALS, SINCE (DO NOT INCLUD) (004) and describe any hed limits (use otherwall)	READ BETWEEN 0 READ BETWEEN 0 BE USED PER MAI TEST 2 UT ATTACHED) LAST MAINTENAN E SIMULATOR TES (.0509) alteration or modifing side if necessary)	1.095% and 0.105% INC 1.038% and 0.042% INC INTENANCE REPORT) 1.099 ICE REPORT, AND NU TS) (.1014) 2 Ication that was made	MBER OF BREA	T3 PT	TOUT ATTACHED) (USE
Run three is spread of .0 RECIRCULA 0.100% S O.040% S O.0	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO ### ### ### ### ### ### ### ### ### #	READ BETWEEN OR READ BETWEEN OR BE USED PER MAINTENAN ESIMULATOR TEST (.0509) alteration or modifier side if necessary) ACCOMPANY SALES AND SA	1.095% and 0.105% INC 1.038% and 0.042% INC INTENANCE REPORT) 1.099 ICE REPORT, AND NU TS) (.1014) 2 ication that was made	MBER OF BREA	T3 FT ATH TESTS restrument	S IN EACH RANGE AS (Over .19) to operate satisfactorily
Run three is spread of .0 RECIRCULA 0.100% S 0.040% S (ONLY ONE EST 1 PERFORM R PERFORM R I NUMBER OF FOLLOWS: FUSALS D tany new parts within establis is to continue to the	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO ### ###############################	READ BETWEEN OR READ BETWEEN OR BE USED PER MAINTENAN ESIMULATOR TEST (.0509) alteration or modifier side if necessary) RED FAID SHIP TEST SALITION AT 340°C 41.	1.095% and 0.105% INC 1.038% and 0.042% INC INTENANCE REPORT) 1.099 INCE REPORT, AND NU TS) (.1014) 2 ication that was made	MBER OF BREA (.1519) to restore the interpretation of the inte	T3 FT ATH TESTS ATH TESTS ATH TESTS	Over .19) D to operate satisfactorily
Run three is spread of .0 RECIRCULA 0.100% S O.40% S O	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO JOGS F.I. TEST (PRINTO REFUSALS, SINCE (DO NOT INCLUD) and describe any hed limits (use other publication). H. SIMULATOR (L.) L. SIMULATOR (L.)	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTENAN TEST 2 THE SIMULATOR TEST SOLUTION OF SIDE OF SI	1.095% and 0.105% INC. 1.038% and 0.042% INC. 1.0999 INCE REPORT, AND NUTS) (.1014) 2 Ication that was made 1.099 (.1014) 3 Ication that was made 1.1014) 3 Ication that was made	MBER OF BREATOR TO TES (.1519) to restore the interpretation of the interpretation in the interpretation i	T3 TATH TESTS ATH TESTS ATH TESTS ATH TESTS ATH TESTS	Over 19) D to operate satisfactorily
Run three is spread of .0 RECIRCULA 0.100% S Q.040% S Q.0	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO "098 F.I. TEST (PRINTO REFUSALS, SINCE (DO NOT INCLUD) and describe any hed limits (use other publication) HETTECHED) SEPERATING (CER	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTENANTEST OF MAINTENANTEST OF SHAPE OF THE STATEST SHAPE OF THE STATEST OF THE	1.095% and 0.105% INC 1.038% and 0.042% INC INTENANCE REPORT) 1.099 ICE REPORT, AND NU TS) (.1014) 2 Ication that was made 1.1014) 2 Ication that was made 1.1014) 3 Ication that was made	MBER OF BREATOR TO TES (.1519) to restore the interpretation of the interpretation in the interpretation i	T3 TATH TESTS ATH TESTS ATH TESTS ATH TESTS ATH TESTS	Over .19) D to operate satisfactorily
Run three is spread of .0 RECIRCULA 0.100% S Q.040% S (ONLY ONE EST 1 PERFORM R PERFORM R I WITHIN EST SOLUTION STRUMENT A PECTING OFFITURE CPL	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO . 098 F.I. TEST (PRINTO REFUSALS, SINCE (DO NOT INCLUD (004) and describe any hed limits (use other of the public of the pub	READ BETWEEN OF READ BETWEEN OF BE USED PER MAINTENANTEST OF MAINTENANTEST OF SHAPE OF THE STATEST SHAPE OF THE STATEST OF THE	1.095% and 0.105% INC. 1.038% and 0.042% INC. 1.099 INTENANCE REPORT, 1.099 ICE REPORT, AND NUTS) (.1014) 2 Ication that was made TYLED BY GAMESTERTIC 2002 SIMMERTOR 1.001 DEPT- OF HE	MBER OF BREAM (.1519) to restore the interpretation of the inter	T3 F ATH TESTS ATH T	Over .19) O to operate satisfactorily CENTRACTO MODEL 19146. PIRES: 7-18-14 MHILED: 1-28-1.
Run three is spread of .0 RECIRCULA 0.100% S Q.040% S (ONLY ONE EST 1 PERFORM R PERFORM R I NUMBER OF FOLLOWS: FUSALS D tany new parts within establish within establish to the stables of the stables o	ests using a stand 05 or less. Check to TION PUMP) TANDARD - MUST TANDARD - MUST STANDARD IS TO . 098 F.I. TEST (PRINTO REFUSALS, SINCE (DO NOT INCLUD (004) and describe any hed limits (use other of the public of the pub	READ BETWEEN OREAD BETWEEN OF BE USED PER MAINTENANTEST (.0509) alteration or modifier side if necessary) AT 3400 H. SALETTO AT 3400 H. SALETT	1.095% and 0.105% INC. 1.038% and 0.042% INC. 1.099 INTENANCE REPORT, 1.099 ICE REPORT, AND NUTS) (.1014) 2 Ication that was made TYLED BY GAMESTERTIC 2002 SIMMERTOR 1.001 DEPT- OF HE	LUSIVE TES MBER OF BREA (.1519) to restore the in the control of the control	T3 F ATH TESTS ATH T	Over .19) O to operate satisfactorily CENTRACTO MODEL 19146. PIRES: 7-18-14 MHILED: 1-28-1.



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 12100 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography on July 20, 2012, using a Perkin Elmer Gas Chromatograph Autosystem XL S/N: 610N9030209, and found to contain 0.1217% (w/vol) ethyl alcohol. The expiration date for this lot number is July 18, 2014 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.100 g/210L +/- 3%.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

NIST Traceability:

Testing was conducted using Cerilliant Reference Standard for number FN122211-02 whose values are traceable to NIST.

All balances are calibrated annually by an outside agency using NIST traceable weights.

Calibration verification is done prior to each use utilizing NIST traveable weights.

JAN 07,2013

FACE THIS SIDE DOWN - THIS EDGE IN FIRST BAC DataMaster

Evidence Ticket

STATE OF MISSOURI
SUNSET HILLS POLICE DEPARTMENT

BAC DATAMASTER SERIAL HUMBER 201190 01/26/13 08:15

--- DIAGNOSTIC CHECK ---

COMPUTERS

OKBY

PROGRAM (04-07-2009);

OKAY

HEATERS

SAMPLE CHAMBER:

480

FLOW DETECTOR:

OKAY

PUMP

HIGH SPEED:

OKAY

DETECTOR:

ÜKAY

FILTERS:

OKAY

QUARTZ STANDARD:

OKAY

CALIBRATION:

OKRY

PRINTER TEST

!"#*%%'()*+,-./0123456789;;<=>?@ABCOEFG HIJKLMNOPQRSTUVWXYZ[\]^_'abcdefghijklmnopqrstuvwxyz{1}-

OPERATOR SIGNATURE

CR Uromi 86

Card Stock No. 60021

REORDER ALL SUPPLIES FROM N.P.A.S. P.O. BOX 1435, MANSFIELD, OH 44901

FACE THIS SIDE DOWN - THIS EDGE IN FIRST

BAC DataMaster

Evidence Ticket

STATE OF MISSOURY...
SUNSET HILLS POLICE DEPARTMENT

DAC DATAMASTER SERIAL NUMBER 201190 01/26/13

TESTING OFFICER:
MORRIS
OFFICER I.D.: 86
PERMIT HUMBER: 220368
EXPIRATION DATE: 10/16/14
MISCELLANEOUS DATA:
TEST

--- SUPERVISOR MODE ---

BLAMK TEST	. 999	08:23
INTERNAL STANDARD	VERIFIED	08:23
EXTERNAL STANDARD	. 898	98:24
BLANK TEST	. 999	98: 24
EXTERNAL STANDARD	.099	08:25
BLANK TEST .	. 999	ú8:25
EXTERNAL STANDARD	.100	98:26
BLANK TEST	. 999	08:26

N = 3 SIM. = .1 AVG. = .099

OPERATOR SIGNATURE

CA llowi 86

Card Stock No.

REORDER ALL SUPPLIES FROM N.P.A.S. P.O. BOX 1435, MANSFIELD, OH 44901

FACE THIS SIDE DOWN - THIS EDGE IN FIRST

BAC DataMaster

Evidence Ticket

STATE OF MISSOURJ.. SUMSET HILLS POLICE DEPARTMENT

DAC DATAMASTER SERIAL NUMBER 201100 01/26/13

ARREST TIME: 03:00 SUBJECT MAME: MORRIS DOB: 19/19/87 SEX: M STATE/D.L.: MO/12345 ARRESTING OFFICER: MORRIS OFFICER I.D.: 86 TESTING OFFICER: MORRIS OFFICER I.D.: 86 PERMIT NUMBER: 220368 EXPIRATION DATE: 10/16/14 MISCELLANEOUS DATA: TEST

--- BREATH AMALYSIS ---

BLANK TEST
INTERNAL STANDARD

. 999

98:32

VERIFIED

08:32

RADIO INTERFERENCE

CR Mounis

OPERATOR SIGNATURE

Card Stock No. 60021

REORDER ALL SUPPLIES FROM N.P.A.S. P.O. BOX 1435, MANSFIELD, OH 44901

State of Missouri DEPARTMENT OF HEALTH



PERMIT TYPE!



ROBERT J MORRIS

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field repairs, and operate the following breath analyzer(s):

DATAMASTER

for the determination of the alcoholic content of blood from a sample of expired (alveolar) air. Issued under the provisions of sections 577.020 through 577.041, RSMo 1986.

10/16/2012	Want
Number 220368	Director of State Public Health Laboratory
Expires 10/16/2014	Margart T. Donnelly
	Director, Department of Health
MO 580-0771 (7-88)	Lab. 4 (R7-88)